



#### **Total Mixed Ration**




#### **Standard Features**

- 1/4" steel drum with stainless liner
- Stainless steel auger trough
- Reversing reel and auger
- Variable speed auger
- Very low maintenance
- No shear pin
- Hay knives spaced 12" apart for effectively processing dry hay
- No ball bearings to fail on reel or auger (Uses UHMW high density poly bearings)
- Gentle tumble mixing action
- 8 models to choose from
- Dual mixing action reel takes feed toward discharge end, auger takes feed away from discharge end, effectively eliminating dead spots.

Heavy duty mixer built for efficiency, safety and years of operation.



Shielded discharge with magnetic strips for cleaner, safer operation.



# Long lasting construction with efficiency in design.

Available in a variety of sizes to meet the needs of most farms.



Large capacity, easy to fill hoppers cut and mix feed smoothly and efficiently.



Electric motors drive auger and mixing reel separately for greater handling options. Large drive gears move material smoothly and efficiently.



## Electra-Mix™ features & options





Efficient heavy duty electrical motors provide reliable performance.



Roller chains with spring-loaded tighteners provide smooth, efficient handling of your ration.





Sealed controls are conveniently placed for safe access. Independent reel/auger switches with variable speed control on auger drive allow you to customize your mix.



An emergency stop is easily accessed from three sides. Equipment stops immediately when cord is pulled. It will only restart by pressing the start button on the control panel.

### **Optional**

Optional Digi Star<sup>™</sup> Electronic Scales will give you desired results in your total mixed ration.

Easily installed with convenient digital readout mounted at desired height.



Digi Star<sup>™</sup> weigh bar



Digi Star<sup>™</sup> readout

### **Electra-Mix™** Specifications

Model No.	1052	862	1062	1262	872	1072	1272	1082	1282
Recommended Mix Capacity (cu ft.)	150	170	215	255	230	290	350	375	450
Reel Capacity (cu ft.)	196	226	282	339	300	384	461	502	602
Approx. No. of Cows Fed	50	56	71	85	76	96	116	125	150
Motor HP	3 & 5	3 & 71/2			3 & 10			5 & 10	
Width (w/o gear reducer mounts*)	61"	73"			85"			97"	
Height (w/scale)	64"	76"			88"			100"	
Length (w/o discharge assembly**)	122"	98"	122"	146"	98"	122"	146"	122"	146"
Discharge Height (w/chute)	15"	20"			26"			30"	
Auger Size	16"			1	9"			24"	
Approx. Shipping Weight	6,000 lbs.	6,500 lbs.	7,500 lbs.	8,300 lbs.	7,800 lbs.	8,900 lbs.	9,900 lbs.	12,000 lbs.	13,000 lbs.

<sup>\*</sup> Electrical panel & motor/gear reducer mounts add approximately 10" to width

Specifications are subject to change without notice.

#### Sized to fit your space and feed handling requirements.



**Authorized Dealer** 

\*\*RISSLER - TMR MIXERS

Toll Free: 1-800-436-5623 Ph: 717-484-0551

Fax: 717-484-1069

448 Orchard Road

Mohnton, PA 19540 USA

<sup>\*\*</sup> Discharge assembly adds approximately 28" to length